

IP dome camera AP-P5080



Characteristics:

3 " metal dome IP camera IR-LED:

28μX3pcs, IR range: 25M darkened

glass, hidden IR-LED video output: 1 x

RJ45 port

Support Onvif, Support Gmail / GOOGLE / QQ / EMAIL PNP (Plug and Play), Support Smartphone and Tablets

OSD, motion detection, remote viewing and control, IR cut

Working temperature: -10°C ~ +60°CSize: 108mm x 88mm

Weight: 450g

Model ID	AP-P5080
description	Metal IR dome IP camera, IR-LED: 28µX3pcs, IR range: 25M
TV system	NTSC / PAL
Video output	1 x RJ45 port
Chipset solution	5.0 megapixels, 3516EV300 + SONY335I 5MP 1 / 2.8 " CMOS sensor
Effective pixels	2560 (H) × 1920 (W)
Minimal lighting	0.001Lux
lens	2.8 mm focal length
synchronization	Internal synchronization
network	1 RJ45 Ethernet interface, 10 / 100M adjustment
Video compression	H.264 compression
Onvif	Support ONVIF
S / N ratio	≥ 58 dB
POE	Integrated PoE
<small>wireless Internet access</small>	Optional
Energy source	DC 12V / 1A
consumption	<5W
Operating environment	- 10 ° C - 60 ° C
Working humidity	≤90%
Size (mm)	108 mm x 88 mm
Weight (kg)	0.45 kg

E-mail: service@blick-store.de

Tel .: +49 2433-9642581

Technical support Monday to Friday from 8:30 a.m. to 12:30 p.m.

If more information is needed, please check first on the www.blick-store.de Additional documents are available in the instructions for the respective product.