

**IN-PS204**

**Data sheet**

## Features:

6x10/100Mbps auto-sensing RJ45 ports, 4x 10/100Mbps PoE ports, 2x uplink port; Supports port auto-flip (Auto MDI/ MDIX); Built-In power supply;

Maximum power of single PoE port: 15.4W/30W;

Adopts store-and-forward architecture; IEEE 802.3af/at power on up to 4 ports;

Features with fanless, natural cooling, small, compact and quiet design, suitable for desktop or wall;

Model		IN-PS204P
Power	Power Adapter Voltage	230V
	Consumption	65W / 120W
Network Connector	Network Port	1 4 Port : 10/100Mbps POE Ethernet Port
		2*Uplink Port : 10/100Mbps Ethernet Port
	Transmission Distance	1~4 Port: Default: 0~100m (10/100Mbps)
		CCTV: 0~250m (10Mbps)
		2*Uplink Port: 100m (100Mbps)
Transmission Medium	Cat5/5e/6 standard network cable	
Network Switch	Network Standard	IEEE 802.3/802.3u, IEEE 802.3x, IEEE 802.1p, IEEE 802.3az
	Switching Capacity	1.2Gbps
	Packet Forwarding Rate	0.8928Mpps
	MAC Table	2K
Power Over Ethernet	PoE Standard	IEEE 802.3af/at
	PoE Power Supply Type	End-Span(1/2+;3/6-)
	PoE Power Consumption	af≤45.4W, at≤30W (every port)
LED Status Indicator	PoE Ethernet LED Indicator	Power: 1 red light indicates that the power normal work;
		POE:4 yellow lights indicate that the POE is power on;
		Ethernet: 6 green lights indicate that the Ethernet link and act;
Environmental	Working temperature	-0 ~55
	Relative Humidity	20~95%
	Storage temperature	-20 ~70
Mechanical	Dimension (LxWxH)	135mm × 88mm × 27mm
	Color	Silver-Gray
	Weight	810g
Stability	MTBF	>30000h

**Email:** [service@blick-store.de](mailto:service@blick-store.de)

**Tel.:** +49 2433-9642580

**Fax:** +49 2433-964258

Technischer Support Montag bis Freitag von 10:00Uhr bis 17:00Uhr

Wenn weitere Informationen benötigt werden überprüfen Sie bitte zuerst ob auf der [www.blick-store.de](http://www.blick-store.de) im Bereich Anleitungen des jeweiligen Produktes zusätzliche Dokumente zur Verfügung stehen.